



HISTERM EPS 50

| Dicke (mm) | Platten in der Packung (Stückzahl) | Packungsmenge (m ²) | Wärmeleitfähigkeit (W/mK) | Wärmewiderstand (m ² K/W) |
|------------|------------------------------------|---------------------------------|---------------------------|--------------------------------------|
| 10 | 50 | 25 | 0,042 | 0,24 |
| 20 | 25 | 12,5 | | 0,48 |
| 30 | 16 | 8 | | 0,71 |
| 40 | 12 | 6 | | 0,95 |
| 50 | 10 | 5 | | 1,19 |
| 60 | 8 | 4 | | 1,43 |
| 70 | 7 | 3,5 | | 1,67 |
| 80 | 6 | 3 | | 1,90 |
| 90 | 5 | 2,5 | | 2,14 |
| 100 | 5 | 2,5 | | 2,38 |
| 110 | 4 | 2 | | 2,62 |
| 120 | 4 | 2 | | 2,86 |
| 130 | 3 | 1,5 | | 3,10 |
| 140 | 3 | 1,5 | | 3,33 |
| 150 | 3 | 1,5 | | 3,57 |

Plattenabmessungen: 1000 x 500 mm

EPS EN 13163-T2-L3-W3-S5-P5-BS75-DS(N)5-CS(10)50